

Trade name: einza Dachbeschichtung, ziegelrot 61-601

Product no.: 0061601

Current version : 4.0.0, issued: 03.08.2023

Replaced version: 3.2.0, issued: 25.11.2021

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

einza Dachbeschichtung, ziegelrot 61-601

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture
coating material

Uses advised against
No data available.

1.3 Details of the supplier of the safety data sheet

Address

einza Farben GmbH & Co KG
Junkersstraße 13
30179 Hannover

Telephone no. +49 (0)511 67490-0
Fax no. +49 (0)511 67490-20
e-mail info@einza.com

Advice on Safety Data Sheet
sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):
+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 3; H412
Skin Sens. 1; H317

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS07

Signal word

Warning

Hazardous component(s) to be indicated on label:

2-octyl-2H-isothiazol-3-one

Hazard statement(s)

H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Trade name: einza Dachbeschichtung, ziegelrot 61-601

Product no.: 0061601

Current version : 4.0.0, issued: 03.08.2023

Replaced version: 3.2.0, issued: 25.11.2021

Region: GB

Hazard statements (EU)

EUH208	Contains 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statement(s)

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear protective gloves/eye protection.
P501	Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]			
	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351i	>= 5.00 - < 10.00	wt%
2	1,2-benzisothiazol-3(2H)-one		pls. refer to footnote (1)	
	2634-33-5 220-120-9 613-088-00-6 -	Acute Tox. 4*; H302 Eye Dam. 1; H318 Skin Irrit. 2; H315 Skin Sens. 1; H317 Acute Tox. 2; H330 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	< 0.05	wt%
3	bronopol			
	52-51-7 200-143-0 603-085-00-8 01-2119980938-15	Acute Tox. 4; H302 Acute Tox. 4; H312 Eye Dam. 1; H318 Skin Irrit. 2; H315 STOT SE 3; H335 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	< 0.10	wt%
4	pyrithione zinc			
	13463-41-7 236-671-3 613-333-00-7 -	Acute Tox. 3; H301 Acute Tox. 2; H330 Eye Dam. 1; H318 Repr. 1B; H360D STOT RE 1; H372 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	< 0.10	wt%
5	terbutryn			

EU safety data sheet



Trade name: einza Dachbeschichtung, ziegelrot 61-601

Product no.: 0061601

Current version : 4.0.0, issued: 03.08.2023

Replaced version: 3.2.0, issued: 25.11.2021

Region: GB

	886-50-0 212-950-5 - -	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Acute Tox. 4; H302 Skin Sens. 1; H317	< 0.025	wt%
6	2-octyl-2H-isothiazol-3-one			
	26530-20-1 247-761-7 613-112-00-5 -	Acute Tox. 3; H301 Acute Tox. 3; H311 Skin Corr. 1; H314 Skin Sens. 1A; H317 Eye Dam. 1; H318 Acute Tox. 2; H330 Aquatic Chronic 1; H410 Aquatic Acute 1; H400 EUH071	< 0.10	wt%
7	2-methyl-2H-isothiazol-3-one			
	2682-20-4 220-239-6 613-326-00-9 -	Acute Tox. 2; H330 Acute Tox. 3; H301 Acute Tox. 3; H311 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 Eye Dam. 1; H318 Skin Corr. 1B; H314 Skin Sens. 1A; H317	< 0.10	wt%
8	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)			
	55965-84-9 - 613-167-00-5 -	Acute Tox. 2; H310 Acute Tox. 2; H330 Acute Tox. 3; H301 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 Eye Dam. 1; H318 Skin Corr. 1C; H314 Skin Sens. 1A; H317	< 0.0015	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(* , ** , *** , ****) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	V, W, 10	-	-	-
2	-	Skin Sens. 1; H317: C >= 0.05%	-	-
3	-	-	M = 10	-
4	-	-	M = 1000	M = 10
5	-	-	M = 100	M = 100
6	-	Skin Sens. 1A; H317: C >= 0.0015%	M = 100	M = 100
7	-	Skin Sens. 1A; H317: C >= 0.0015%	M = 10	M = 1
8	B	Skin Sens. 1A; H317: C >= 0.0015% Eye Irrit. 2; H319: C >= 0.06% Skin Irrit. 2; H315: C >= 0.06% Skin Corr. 1C; H314: C >= 0.6% Eye Dam. 1; H318: C >= 0.6%	M = 100	M = 100

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

No	Route, target organ, concrete effect
1	H351i inhalational; -; -

SECTION 4: First aid measures

Trade name: einza Dachbeschichtung, ziegelrot 61-601

Product no.: 0061601

Current version : 4.0.0, issued: 03.08.2023

Replaced version: 3.2.0, issued: 25.11.2021

Region: GB

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Not combustible under normal conditions. Extinguishing measures to suit surroundings.

Unsuitable extinguishing media

No data available.

5.2 Special hazards arising from the substance or mixture

None known.

5.3 Advice for firefighters

Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Trade name: einza Dachbeschichtung, ziegelrot 61-601

Product no.: 0061601

Current version : 4.0.0, issued: 03.08.2023

Replaced version: 3.2.0, issued: 25.11.2021

Region: GB

Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

No special measures necessary.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Comply with legal health and safety regulations; Prevent unauthorised access. No smoking. Keep from freezing.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]	13463-67-7	236-675-5
List of approved workplace exposure limits (WELs) / EH40			
Titanium dioxide			
total inhalable dust			
	WEL long-term (8-hr TWA reference period)	10	mg/m ³
List of approved workplace exposure limits (WELs) / EH40			
Titanium dioxide			
respirable dust			
	WEL long-term (8-hr TWA reference period)	4	mg/m ³

DNEL, DMEL and PNEC values**DNEL values (worker)**

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]			13463-67-7 236-675-5	
	inhalative	Long term (chronic)	local	1.25	mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]			13463-67-7 236-675-5	
	inhalative	Long term (chronic)	local	210	$\mu\text{g}/\text{m}^3$

8.2 Exposure controls**Appropriate engineering controls**

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal protective equipment

Trade name: einza Dachbeschichtung, ziegelrot 61-601

Product no.: 0061601

Current version : 4.0.0, issued: 03.08.2023

Replaced version: 3.2.0, issued: 25.11.2021

Region: GB

Respiratory protection

Not necessary. When applied by spraying: Filter A2P2 (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	In case of short-term contact / splash protection: nitrile rubber		
Material thickness	>	0.4	mm
Breakthrough time	>	120	min
Appropriate Material	In case of prolonged exposure: nitrile rubber		
Material thickness	>	0.4	mm
Breakthrough time	>	480	min

Other

Light protective clothing

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	
liquid	
Form	
liquid	
Colour	
according to product name	
Odour	
characteristic	
pH value	
Value	7.0 - 9.0
Boiling point / boiling range	
Value	100 °C
Melting point/freezing point	
No data available	
Decomposition temperature	
No data available	
Flash point	
Not applicable	
Ignition temperature	
No data available	
Oxidising properties	
Not applicable	
Flammability	
Not applicable	
Lower explosion limit	
No data available	

Trade name: einza Dachbeschichtung, ziegelrot 61-601

Product no.: 0061601

Current version : 4.0.0, issued: 03.08.2023

Replaced version: 3.2.0, issued: 25.11.2021

Region: GB

Upper explosion limit	
No data available	

Vapour pressure	
Value	< 100 hPa
Reference temperature	50 °C

Relative vapour density	
No data available	

Relative density	
No data available	

Density	
Value	1.00 - 1.70 g/cm ³
Reference temperature	25 °C
Method	DIN 51757

Solubility in water	
Comments	miscible

Solubility	
No data available	

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Not applicable			
Source		ECHA	

Kinematic viscosity	
Value	1000 - 8000 mPa*s
Reference temperature	25 °C
Method	DIN 53019

Solvent separation test	
Not applicable	

Particle characteristics	
No data available	

9.2 Other information

Other information	
No data available.	

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

Trade name: einzA Dachbeschichtung, ziegelrot 61-601

Product no.: 0061601

Current version : 4.0.0, issued: 03.08.2023

Replaced version: 3.2.0, issued: 25.11.2021

Region: GB

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Acute dermal toxicity			
No data available			

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
LC50		5.09	mg/l
Duration of exposure		4	h
State of aggregation	Dust		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Route of exposure	Skin		
Species	mouse		
Method	OECD 429		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Trade name: einzA Dachbeschichtung, ziegelrot 61-601

Product no.: 0061601

Current version : 4.0.0, issued: 03.08.2023

Replaced version: 3.2.0, issued: 25.11.2021

Region: GB

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Type of examination		In vitro mammalian cytogenicity	
Method		OECD 487	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Route of exposure		oral	
Type of examination		In vivo mammalian somatic cell study: cytogenicity / erythrocyte micronucleus	
Species		rat	
Method		OECD 474	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Route of exposure		oral	
NOAEL		>=	1000 mg/kg bw/d
Type of examination		Reproductive studies - one generation	
Species		rat	
Method		OECD 443	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Route of exposure		oral	
NOAEL		>=	1000 mg/kg bw/d
Type of examination		Prenatal Developmental Toxicity Study	
Species		rat	
Method		OECD 414	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Route of exposure		oral	
NOEL		>=	7500 mg/kg bw/d
Species		mouse	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
STOT - single exposure			
No data available			
STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Route of exposure		oral	
NOAEL		>	962 mg/kg bw/d
Species		rat	
Method		OECD 408	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Route of exposure		inhalational	

Trade name: einza Dachbeschichtung, ziegelrot 61-601

Product no.: 0061601

Current version : 4.0.0, issued: 03.08.2023

Replaced version: 3.2.0, issued: 25.11.2021

Region: GB

Species	rat
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Aspiration hazard
No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure
The liquid splashed in the eyes may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)
No data available

Toxicity to fish (chronic)
No data available

Toxicity to Daphnia (acute)
No data available

Toxicity to Daphnia (chronic)
No data available

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
EC50	>	100	mg/l
Duration of exposure		72	h
Species	Raphidocelis subcapitata		
Method	OECD 201		
Source	ECHA		
Evaluation/classification	Based on the available data, the classification criteria are not met.		

Toxicity to algae (chronic)
No data available

Bacteria toxicity
No data available

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Source	ECHA		
Evaluation	Not applicable for inorganic substances.		

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.

Trade name: einza Dachbeschichtung, ziegelrot 61-601

Product no.: 0061601

Current version : 4.0.0, issued: 03.08.2023

Replaced version: 3.2.0, issued: 25.11.2021

Region: GB

1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Not applicable Source		ECHA	

12.4 Mobility in soil
No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties
No data available.

12.7 Other adverse effects
No data available.

12.8 Other information

Other information
Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 01 12 waste paint and varnish other than those mentioned in 08 01 11
The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

14.2 Transport IMDG

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

Trade name: einzA Dachbeschichtung, ziegelrot 61-601

Product no.: 0061601

Current version : 4.0.0, issued: 03.08.2023

Replaced version: 3.2.0, issued: 25.11.2021

Region: GB

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	1,2-benzisothiazol-3(2H)-one	2634-33-5	220-120-9	75
2	2-amino-2-methylpropanol	124-68-5	204-709-8	75
3	2-octyl-2H-isothiazol-3-one	26530-20-1	247-761-7	75
4	bronopol	52-51-7	200-143-0	75
5	diiron trioxide	1309-37-1	215-168-2	75
6	Iron hydroxide oxide yellow	51274-00-1	257-098-5	75
7	Limestone	1317-65-3	215-279-6	75
8	pyrithione zinc	13463-41-7	236-671-3	75
9	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5	75
10	triiron-tetraoxide	1317-61-9	215-277-5	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE , Cat. : c, type: wb = 100 g/l
Max. VOC content (limit value) of the product in its ready for use condition = < 100 g/l

National regulations

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH071

Corrosive to the respiratory tract.

Trade name: einzA Dachbeschichtung, ziegelrot 61-601

Product no.: 0061601

Current version : 4.0.0, issued: 03.08.2023

Replaced version: 3.2.0, issued: 25.11.2021

Region: GB

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H351i	Suspected of causing cancer by inhalation.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

B	Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.
V	If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.
W	It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.
1	The concentration stated or, in the absence of such concentrations, the generic concentrations of this Regulation (Table 3.1) or the generic concentrations of Directive 1999/45/EC (Table 3.2), are the percentages by weight of the metallic element calculated with reference to the total weight of the mixture.

Creation of the safety data sheet

UMCO GmbH
Georg-Wilhelm-Str. 187, D-21107 Hamburg
Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.
The safety data sheet describes products with a view to safety requirements.
It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:
Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.
Prod-ID 725373